



General Information

C type is the CBE, dedicated to R744 (CO₂), and compatible with heat pump and refrigeration system. The model has three types, including 70/100/140 BAR. The compact design plus outstanding thermal transfer efficiency and low pressure drop characterize C series. C020 can sustain 70BAR and afford 8kW heat exchange. It is suitable for evaporator and condenser in refrigeration and freezing storage.

Industries

HVAC, Refrigeration, Heat Pump

Connection (up to)



Male Thread

Female Thread

Applications

Evaporator, Condenser, De-superheater/Subcooler, Economizer,
Pre-cooler/Pre-heater



Solder

**Depends on working
condition**

Max. Heat Transfer Capacity



Specifications

Standard Materials

Cover Plates

Stainless Steel

Connections

Stainless Steel

Plates

Stainless Steel

Braze Material

Copper

Standard Data

Max. working temperature °C

200

Max. working pressure (bar)

70

Min. test pressure (bar)

100

Max. flow rate (LPM)

N/A

Max. number of plates (N)

80

Plate Heat Transfer Area (M²)



0.01109 m²

Thickness (mm) - H

9.5+1.1*N

Weight (kg)

1.12+0.042N



(size: mm)

(without connection)

N: Number of Plates

Material disclaimer

This information is intended to serve as a reference and is not subject to guarantee. Precise inquiries are necessary for accurate information regarding performance specifications and suitability under specific working conditions. Responsibility rests on purchasers to decide whether products are appropriate for use before purchasing. Kaori is not liable for corrosion of products and/or other equipment from use of products. Kaori reserves the right to make changes to this information without prior notice. Third party approvals and certifications are available upon request.

Kaori Heat Treatment Co., Ltd. Innovation • Quality • Responsibility • Honor